








Introduction:

Geometric and minimalistic styling define the Nulo showering range from Inta. Combined with its thermostatic protection and innovative features to aid installation, it's a popular and reliable choice time after time. The Nulo range has it all.

Features

-  Thermostatic Anti-Scald Protection
-  Safe Touch Body
-  WRAS and TMV2 Approved Valve
-  Push Button Handset with Aerating Spa Jet
-  Pivoting Slide Rail Kit

Product Range

Description	Code
Deluxe Nulo Safe Touch Thermostatic Single Outlet Bar Shower with Flexible Slide Rail Kit , Smooth Hose and Push Button Handset	CB10035CP



Nulo showers have been accredited TMV2 approval from BuildCert where you see this logo.



The constant circulation of cold water under the surface of the valves ensures the surface will never be hot to touch.



All Nulo bar showers feature Inta's proven anti-scald thermostatic technology.



Nulo showers have been approved by WRAS where you see this logo.

Technical Specification

Minimum Inlet Pressure: 0.2 Bar (dynamic)

Maximum Inlet Pressure: 5 Bar (static)

Inlet Connections: 3/4" (valve body)

Outlet Connection: G1/2"

Factory Pre-set Temperature: 38°C

Minimum Inlet Temperature Differential: 15°C

