

shower valves - Puro Thermostatic Shower

**mini shower,
big performance
and peace of mind,
protection**

Introduction

The all new Puro collection from Inta is defined by the unique contemporary styling, high showering performance and energy saving eco-air shower heads. The Puro Mini is the ultimate combination of form and function delivering large flow rates from a mini shower body and featuring Inta's proven anti-scald thermostatic technology you can bring inspiration, performance and peace of mind protection to your bathroom with Inta's mighty Puro Mini Shower.



PU90014CP

- High flow rate at low pressure
- Universal exposed or concealed solution in one box
- Water saving eco air handset
- Serviceable inlets
- Thermostatic anti-scald technology with Fail safe protection on both hot and cold supplies
- 110mm & 150mm Inlet connections included in the one box solution
- Temperature stability of +/-2°C
- Fail safe on hot and cold supplies
- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- WRAS and TMV2 approved

Product Range

Description	Code
Puro thermostatic mini concentric dual control shower with flexible slide rail kit and eco air handset - exposed/concealed	PU90014CP



shower valves - Puro Thermostatic Shower

Technical Specification

Max Inlet Pressure static	5 Bar
Min Inlet Pressure dynamic	0.2 Bar
Max Inlet Temperature	85°C
Factory Pre-set Temperature	41°C
Inlet Connections for PU90014CP	15mm Compression
Outlet Connections	G1/2" BSP
Min Temperature to achieve hot or cold failsafe	15°C
System Installation	Unvented, Pressurised, Gravity and Combination Boilers

