

ball **UNIVERSAL GAS/WATER**BALL VALVES

Introduction

Intas range of universal gas and WRAS approved ball valves are the installers choice for safe, industry compliant gas and potable water installations. In addition to fully meeting the requirement of BS EN 331:1998+A1:2010, inta's range of 15,22 & 28mm gas ball valves are also WRAS approved making them suitable for use on potable water systems. Each valve is supplied with yellow, red and blue lever sleeves meaning the installer can denote the use of the valve depending on the installation.



- Meets the requirements of BS EN 331:1998+A1:2010
- WRAS approved
- Independently assessed and certified
- Suitable for hot and cold water and gas installations
- Available in 15, 22 & 28mm lever handle ball vales
- Supplied with yellow, blue and red lever handle sleeves
- Temperature rating for gas application -20°C 60°C
- Temperature rating for non-gas application -20°C 110°C
- Pressure rating PN16

Product Range

| 15mm universal gas/water lever ball valve | IN89ALGWC15 |
|---|-------------|
| 22mm universal gas/water lever ball valve | IN89ALGWC22 |
| 28mm universal gas/water lever ball valve | IN89ALGWC28 |
| 35mm universal gas/water lever ball valve | IN89ALGWC35 |
| 42mm universal gas/water lever ball valve | IN89ALGWC42 |
| 54mm universal gas/water lever ball valve | IN89ALGWC54 |
| ½" universal gas/water lever ball valve | IN90ALGWP15 |
| 3/4" universal gas/water lever ball valve | IN90ALGWP20 |
| 1" universal gas/water lever ball valve | IN90ALGWP25 |
| 1¼" universal gas/water lever ball valve | IN90ALGWP32 |
| 1½" universal gas/water lever ball valve | IN90ALGWP40 |
| 2" universal gas/water lever ball valve | IN90ALGWP50 |
| | |

